

## APC-3920T

19" LCD 第 4 世代 Haswell 4th Generation  
Intel i3/i5/i7 アルミ製のベゼルと筐体を採用  
明るさ調整つまみ 0%~100%  
パネル表面の反射を低減させる AR Touch Screen  
and AR Protection Glass (オプション)



<b>CPU</b>	第 4 世代 Core i3/i5/i7 Haswell-ULT i3-4010U 1.70GHz (15W) default
<b>Chipset</b>	SoC
<b>Memory</b>	Onboard 4GB DDR3L 1600 MHz
<b>USB</b>	2 x USB 3.0 type A, 1 x USB 2.0 type A(at front bezel with IP65 Cover)
<b>Serial</b>	1 x RS-232/422/485 selectable default RS-485 DB9(COM1) 2 x RS-232 DB9 (COM3/4) 1 x RS-422/485 with isolation DB9 (Optional)
<b>Audio</b>	1 x Line-out phone jack
<b>LAN</b>	2 x GbE RJ-45
<b>Membrane control</b>	1 x VR Dimm-Knob for 0%~100% brightness control (at front bezel with IP65 design), 1 x Backlight on/off and touch on/off button
<b>Power</b>	1 x 3pin DC power connector, 1 x ESD ground
<b>HDD</b>	1 x 2.5" SATA2 Easily Accessible storage design
<b>SD</b>	1 x Internal SD slot on board
<b>拡張スロット</b>	2 x Mini PCIe full size
<b>サイズ</b>	19" TFT-LCD
<b>解像度</b>	1280 x 1024
<b>最大色数</b>	16.2M
<b>輝度</b>	(cd/m <sup>2</sup> ) 350
<b>視野角</b>	(H° / V° ) 170/160
<b>コントラスト比</b>	1000:1
<b>BacklightMTBF</b>	50000 時間
<b>Touch Screen</b>	TypeResistive (InterfaceUSB)
<b>Light transmission</b>	80%
<b>Power input</b>	9~36V DC
<b>構造</b>	Aluminum (10mm) bezel and Aluminum housing (Anti-Corrosion Coating)
<b>IP</b>	Front bezel IP65
<b>外形寸法</b>	484 x 400 x 65
<b>質量</b>	10.0kg
<b>使用周囲温度</b>	(° C) 0~50 / -20~60 (with Industrial storage for option)
<b>保存周囲温度</b>	(° C) -30~70
<b>使用周囲湿度</b>	10 to 90% @ 40° C, non-condensing
<b>適合規格</b>	CE/FCC Class B/IEC 60945/ (Meet IACS E10/DNV)
<b>サポート OS</b>	Windows 7 pro for embedded, Windows embedded standard 7, Windows Embedded Enterprise 8, Windows Embedded Standard 8



東京都豊島区池袋2-54-12  
日宝池袋第一ビル 1F  
TEL.03-5952-5396/FAX.03-5952-5398