

LC-712

2コア4スレッドのTDP3.5Wの低消費電力タイプ
薄型タイプ(t=40mm)の省スペース IP65 対応
12インチ TFT LCD,WiFi オプション



| | |
|-----------------|---|
| CPU | Intel® Atom™ Processor N2600 1.6GHz |
| メモリ | Soldered onboard 2GB DDR3 SDRAM |
| Chipset | Intel® NM10 |
| LAN | 2 x Intel® 82583V GbE controllers |
| Watchdog Timer | 1~255 levels reset |
| ストレージ | フロントアクセス可能な CFast & 2.5" drive bay |
| Audio | Speaker , 2 x 1.5W speakers (optional) |
| LCD Size | 12.1" TFT LCD Panel |
| Max. Resolution | 1024 x 768, XGA |
| Max. Colors | 16.2M |
| Luminance | 500 cd/m ² |
| Touch Screen | 5-wire Analog Resistive |
| 視野角 (上下/左右) | 70° /70° /80° /80° |
| Function Key | Brightness up/down, Screen on/off |
| LED Indicator | Power on LED |
| Power Input | DC 9~36V |
| 拡張 Bus | 1 x Mini-card socket |
| 適合規格 | EMC / EMI 、 CE, FCC Class B |
| Serial Port | 4 x DB-9 connectors for COM1~4 (COM1 and COM2 are RS-232; COM3 and COM4 are RS-232/485 configurable) |
| USB Port | 4 x Type-A USB 2.0 ports (rear) 1 x Type-A USB 2.0 port with rubber cover on front bezel |
| LAN | 2 x RJ-45 GbE ports |
| DVI | 1 x DVI connector |
| WiFi | 2 x SMA antenna holes for optional WiFi function |
| Mounting Type | Panel Mounting and VESA-75/100 Mounting |
| Chassis | Panel-mounting chassis, aluminum front bezel and SECC steel chassis |
| 外形寸法 | 325.88W x 258.86H x 44.0D mm |
| Weight (Net) | 2.2 kg (without VESA bracket) |
| 使用周囲温度 | -20 ~ 55°C (-4 ~ 131° F) |
| 保存周囲温度 | -20 ~ 70° C (-4 ~ 158° F) |
| 使用周囲湿度 | 10 ~ 95% RH @ 55° C (non-condensing) |
| 振動 | 5 ~ 500Hz, 2Grms X,Y,Z axis (with CF/SSD) |
| 衝撃 | Operating 20G, 11ms X,Y,Z axis (with CF/SSD) |
| サポート OS | Win XP Embe / Windows Embe 7/Windows Embe Compact 7 / Linux Kernel 2.6 |



東京都豊島区池袋2-54-12
日宝池袋第一ビル 1F
TEL:03-5952-5396/FAX:03-5952-5398