

# LC7123...12.1”LCD ,Atom N2600



広範囲の温度域で使用可能 -20 ~ 55°C

2 コア 4 スレッドの TDP3.5W の低消費電力タイプ

薄型タイプ(t=45mm)の省スペース IP65 対応

WiFi オプション、画面の明るさ調整可

<b>CPU</b>	Intel® Atom™ Processor N2600 1.6GHz
<b>Memory</b>	Soldered onboard 2GB DDR3 SDRAM
<b>Chipset</b>	Intel® NM10
<b>LAN</b>	2 x Intel® 82583V GbE controllers
<b>Watchdog Timer</b>	1~255 levels reset
<b>Storage</b>	フロントアクセス可能な CFast & 2.5” drive bay
<b>Audio</b>	2 x 1W speakers , 1 x Line-out phone jack
<b>LCD Size/Type</b>	12.1" TFT LCD Panel
<b>解像度</b>	1024 x 768, XGA
<b>最大色数</b>	16.2M
<b>輝度</b>	500 cd/m <sup>2</sup>
<b>Touch Screen</b>	5-wire Analog Resistive
<b>視野角 (上下/左右)</b>	80°/80°/70°/70°
<b>調整つまみ</b>	Brightness up/down, Screen on/off, Power on/off、
<b>LED Indicator</b>	Power on LED
<b>Power Input</b>	DC 9~36V
<b>EMC / EMI</b>	CE, FCC Class A
<b>拡張 Bus</b>	1 x Mini-card socket , 1 x Internal USB dongle space
<b>Serial Port</b>	1 x DB-44 connector for COM1~4
<b>USB Port</b>	4 x Type-A USB 2.0 ports
<b>LAN</b>	2 x RJ-45 GbE ports
<b>DVI</b>	1 x DVI-I connector (DVI-D + VGA)
<b>DIO</b>	1 x DB-26 connector (8 x isolated programmable DIO, 4 x digital inputs & 4 x digital
<b>WiFi</b>	2 x SMA antenna holes for optional WiFi function
<b>Mounting Type</b>	Panel Mounting and VESA-75/100 Mounting
<b>Chassis</b>	Panel-mounting chassis, aluminum front bezel and SECC steel chassis
<b>Dimension (W x H x D)</b>	326.00 x 259.00 x 45.50 mm (12.8" x 10.2" x 1.79")
<b>Weight (Net)</b>	2.4 kg (without VESA bracket)
<b>使用周囲温度.</b>	-20 ~ 55°C (-4 ~ 131°F)
<b>保存周囲温度</b>	-20 ~ 70°C (-4 ~ 158°F)
<b>使用周囲湿度</b>	10 ~ 95% RH @ 55°C (non-condensing)
<b>対振動</b>	5 ~ 500Hz, 2Grms X,Y,Z axis (with CF/SSD)
<b>耐衝撃</b>	Operating 20G, 11ms X,Y,Z axis (with CF/SSD)



日本ノヴァシステム株式会社

東京都豊島区池袋2-54-12

日宝池袋第一ビル 1F

TEL:03-5952-5396/FAX:03-5952-5398