

Vitro5815(5819)

Vitro5000 シリーズはガラス越しのタッチ操作が可能なパネルコンピュータです。

15,19 インチの完全なフラット画面 IP66 対応

バックライトに LED

輝度 1000nits(オプション)



VariVitro 815 & 819

CPU	Intel Core i3-2330E 2.2GHz with L3 Cache 3MB Intel Core i5-2510E 2.5GHz with L3 Cache 3MB Intel® Mobile Celeron B810 1.6GHz with L3 Cache 2MB
Chipset	Intel HM65
System Memory	1 x SO-DIMM DDRIII 1333, up to 8GB
LCD	投影型静電容量方式
TFT LCD	(VariVitro 815) 15" or (VariVitro 819) 19" LED backlight
輝度	400 nits / 1000 nits (optional)
解像度	1280 x 1024
Touch Screen	15" or 19" True Flat Projected Capacitive Technology
使用可ガラス厚	Max. 10mm
ストレージ	
HDD Type	1 x SATA 6.4cm (2.5")HDD
SSD Type	1 x SATA 6.4cm (2.5") SSD (optional)
Compact Flash Type	N/A
I/O	
DC Input	1 x Mini Din 4P (DC 12V only)
Cash Drawer	1 x RJ-11 (Power Pin 12V)
Network (LAN)	1 x Gigabit Ethernet by RJ-45
USB Port	4 x USB 2.0
Serial Port	4 x RS-232 w/ RI/5V/12V power

	(COM1/2: DB-9, COM3/4 : RJ-48)
Audio	1 x Line out / MIC in
PS/2 Port	1 x PS/2 Keyboard
LPT Port	1 x Parallel port
VGA Port	1 X D-sub VGA
Audio	HD Audio compliant, 2W Speaker x 2
Bus Expansion	1 x Mini-PCI-E Slot
Compliance	IP 66 on front panel
System Management	Desktop Management Interface (DMI)
	Preboot Execution Environment (PXE)
	Wake on LAN (WoL)
	Advanced Configuration and Power Interface (ACPI)
サポート OS	Win 7, Win POSReady, Win XP Pro for Embedded, Fedora(Linux)
Power Supply	External adapter, DC Model:120 Watts, Voltage:+12VDC 10A max.
本体材質	Main Unit: Die-casting aluminum ; I/O Cover:Plastic
色	Main Unit: Black / White
適合規格	CE, FCC, Class-B, RoHS, WEEE
外形寸法	446W x 377H x 70D mm
質量	7.3 Kg
VESA	100 x 100 mm
使用周囲温度	0°C ~ 40°C, 10% ~ 90% RH, non-condensing
保存周囲温度	-20°C ~ 60°C, 10% ~ 90% RH, non-condensing