

# S15AB

寒冷地から高温地域での過酷な温度にも耐えるノート PC。防塵・防滴設計の IP53 対応

米国国防総省基準準拠...落下テスト/耐衝撃・耐振動

セキュリティ<vPro , Computrace Ready ,指紋スキャナ ,ステルスモード ,セキュリティロック>

ホットスワップ対応のバッテリー使用で 12 時間駆動



## Rugged Features

- Drop
  - 2.5 feet drops on 6 faces
- Vibration
  - MIL-STD 810G 514.6, Cat.4, Fig 514.6C-1(Operating)
  - ASTM 4169-08 Truck Transport, 11.5.2 Random test, Assurance Level II(Operating)
- Spill-proof keyboard, touchpad, buttons
- Magnesium Alloy Chassis

## Environment

- Temperature
  - Operating: 0°C~ 50°C
  - Storage: -40°C~71°C
- Humidity
  - Operating: 5% ~ 95%
- Altitude
  - Operating: 15,000 feet
  - Storage 40,000 feet

## Operating System

- Genuine Windows 8.1 Professional
- Genuine Windows 10 Professional

## Processor

- Intel 5th Generation Broadwell U series CPU platform

## System Memory

- Two DDR3 sockets (Max. 16GB)

## Mass Storage

- 2.5" SATA3 HDD 500 GB ~ 1TB or SSD 128GB ~ 512GB

## Display

- 15.6" FHD (1920x1080) TFT LCD

## Multimedia Bay

- 5.25"/9.5mm Super-multi ODD or Blu-ray Drive Writer

## Audio

- Intel High Definition Audio
- Speaker x 2 / 80dB
- Microphone x 2

## Camera

- 2.0 Mega-pixel Web-Cam with Mic

## Communication

- Integrated Gigabit Ethernet with RJ45 connector
- WLAN 2x2 a/b/g/n/AC
- Bluetooth 4.0 Class1
- LTE WWAN1
- GPS1

## Security

- Computrace® Ready
- TPM 2.0
- Smart Card Reader
- Kensington Lock

## Expansion Slots

- Built-in SD Card & Support SDXC Card Reader

---

	<ul style="list-style-type: none"><li>● Smart Card Reader</li></ul>
<b>I/O Ports</b>	<ul style="list-style-type: none"><li>● Two USB3.0</li><li>● Two USB2.0</li><li>● One headphone jack / MIC combo jack</li><li>● One VGA port</li><li>● One RJ-45</li><li>● One HDMI Support to 4K resolution</li><li>● One RS232 port</li><li>● One DC-In</li></ul>
<b>Battery</b>	<ul style="list-style-type: none"><li>● Lithium polymer battery pack: 8.5 hrs</li></ul>
<b>AC Adaptor</b>	<ul style="list-style-type: none"><li>● 110V - 240V; 65W</li><li>● 375 mm (W) x 273 mm (L) x 29.5 mm (H)</li><li>● 2.6 Kg/5.90 lbs</li></ul>

---



**日本ノヴァシステム株式会社**

東京都豊島区池袋2-54-12  
日宝池袋第一ビル 1F  
TEL:03-5952-5396/FAX:03-5952-5398